CERTIFICATE OF COMPLIANCE

Certificate Number	E312057
Report Reference	E312057-20140718
Issue Date	2020-APRIL-23
Issued to:	Dewit Industrial Sensors BV Oostergracht 40 3763 LZ Soest Netherlands
This certificate confirms that representative samples of	Proximity Switches Refer to the Addendum Page for Models
	Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.
Standard(s) for Safety:	UL 60947-5-2, and CSA C22.2 No. 60947-5-2-14, Low-Voltage Switchgear and Controlgear - Part 5-2: Control Circuit Devices And Switching Elements - Proximity Switches UL 60947-1 and CSA C22.2 No. 60947-1-13, Low-Voltage Switchgear and Controlgear - Part 1: General Rules
Additional Information:	See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

CERTIFICATE OF COMPLIANCE

Certificate Number	E312057
Report Reference	E312057-20140718
Issue Date	2020-APRIL-23

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Class 2, Proximity switches, Inclination sensors, Series QG, followed by numbers , may be followed by N, P, D, B, X or empty space, may be followed by 2, 3, or empty space, followed by K, M, C or S, followed by I, D, G, or A, followed by X, Y, Z, O or any combination of these characters, or empty space, followed by h, v, hv or empty space, followed by any number between 0.1 and 200, or by any number between 001 and 999, followed by E, H, X, S, L, M, or empty space, followed by 2 or empty space, followed by AV, AV2, AV3, AV4, AV5, AI, IO, ASN, ASP, ASC, SPI, I2C, CAN, CANJ, CANS, PWM, 485, MOD, S, W, or 232, ,or any combination, may be followed by any number between 0.1 and 2.7, or empty space, followed by, C, M, S, F, or any combination of these letters, or Pty.zCS4p, where y and z can indicate any number between 0 and 9, may be followed by any number(s), followed by 5V or empty space, followed by UL, may be followed by any combination of characters.

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000