QG series

QG65D Analog Standard accuracy series

QG65D-KDXYh-030-AI-CM-UL

Dynamic Inclination sensor

2 axis horizontal mounting

Factory programmable device
Output: 4 - 20 mA

Measuring range programmable between ±1° and ±30°

Measuring range
Factory defaults: ± 30°



c UL us LISTED E312057

CE

General specifications 14335, v20250811	
Housing	Reinforced plastic injection molded (Faradex DS, black, EMI shielded by stainless steel fiber in PC)
Dimensions (indicative)	60x50x27 mm
Mounting	Not included: M5 pan head screws. Mounting on flat surface only. Screw with care
Ingress Protection (IEC 60529)	IP67, IP69K (with IP69K mating connector)
Relative humidity	0 - 95% (non condensing, housing fully potted)
Weight	approx. 110 gram
Supply voltage	10 - 32 V dc
Polarity protection	Yes
Current consumption	≤ 25 mA (excluding output signal)
Operating temperature	-40 .. +80 °C
Storage temperature	-40 .. +85 °C
Measuring range	Factory defaults: ± 30°
Centering function	Yes (12 mA = 0°), range: ±5°
Frequency response (-3dB)	0 - 50 Hz, Max angle rate 500°/s
Accuracy (overall @20°C)	± 0,2° 2σ
Non linearity	± 0,18° 2σ
Resolution	0,01°
Temperature coefficient	± 0,01°/K typ. (over full temperature range)
Max mechanical shock	10,000g (max 0,2ms, non-repetitive)
Output	4 - 20 mA
Output load	0 ≤ Rload ≤ (Vcc-3) / 20mA (Ω), 32 ≥ Vcc ≥ 3+(Rload * 20) (V)
Short circuit protection	Yes
Output refresh rate	10 ms
Programming options	Factory programmable (measuring range, filtering)

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

QG series


QG65D-KDXYh-030-AI-CM-UL

Iout = 12 + 8*(α/30) [mA]

Clipping outside measuring range

Zero adjustment: eliminate mech. offsets
Connect zero adjustment input to ground (>0,5sec) within 1 min. after power up. Normally this input should be left unconnected or permanent connected to Gnd

Transfer characteristic




Default 0°: horizontal (label upwards), no acceleration applied.

Cross tilt sensitivity error:
< (0,12 * cross tilt angle)² % typ.

→ one axis <10° tilt for max. accuracy

Measurement orientation




Connectivity (cable length ±10%)

Connection	M12 male 5p A-coding connector (Brass Nickel coated, contacts copper alloy)
Wire / pin coding	
Pin 1:	+ Supply voltage
Pin 2:	Output Y
Pin 3:	Gnd
Pin 4:	Output X
Pin 5:	Zero adjustment input



Mechanical dimensions (indicative only)



Remarks, Installation instructions, UL

QG series sensors are intended to measure inclination/acceleration/tilt. Flawless function (acc. spec.) is ensured only when used within specifications. This device is not a safety component acc. to EU Machine Directive (ISO13849). For full redundancy two devices can be used. Modifications or non-approved use will result in loss of warranty and void any claims against the manufacturer.

UL & c-UL listed product (File number E312057, UL508 standards UL60947-5-2 & CSA-C22,2 No. 14)
Product Identity / Category Code Number (CCN): Industrial Control Equipment / NRKH & NRKH7
Enclosure rating: type 1, Ambient temperature: max 80 °C (see also datasheet, lowest value applies)
Electrical ratings: Intended to be used with a Class 2 power source in accordance with UL1310,

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

	max. input Voltage 32V dc (see also datasheet, lowest value applies), max. current 200mA Accessory Cable Assembly: Any UL-listed (CYJV/7) mating connector with mechanical locking, wire thickness of at least 30 AWG (0,05 mm²), recommended ≤23 AWG (≥0,25 mm²) Installation instructions: 1. The cable must always be used as a whole (wires may not be separated from each other) 2. For the automotive (non-R10) standards ISO 13766-1 and -2 (earth moving machinery) and ISO 14982 (agricultural), the sensor may not be directly powered from the vehicle's battery. As this device is accelerometer-based the sensor is inherent sensitive for accelerations/vibrations. Application specific testing must be carried out to check whether this sensor will fulfil your requirements. Before using this device, please read this datasheet, the Manual and the Declaration of Conformity carefully (download from dis-sensors.com)

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000