# QG series

## QG65D SAE J1939 High accuracy series

QG65D-KDXYh-030H-CANJ-C(F)M-UL

**Dynamic Inclination sensor**
2 axis horizontal mounting

Programmable device
Interface: CAN SAE J1939

Parameters programmable
by J1939

Measuring range
± 30°



| | **General specifications** 14007, 14010, v20241115 |
|---|---|
| Housing | Reinforced plastic injection molded (Faradex DS, black, EMI shielded by stainless steel fiber in PC) |
| Dimensions (indicative) | 60x50x27 mm |
| Mounting | Included: 4x M5x25 mm zinc plated steel pozidrive pan head screws, self-tapping (PZ DIN7500CZ)<br>Mounting on flat surface only. Screw with care |
| Ingress Protection (IEC 60529) | IP67, IP69K (with IP69K mating connector) |
| Relative humidity | 0 - 95% (non condensing, housing fully potted) |
| Weight | approx. 110 gram |
| Supply voltage | 10 - 32 V dc |
| Polarity protection | Yes |
| Current consumption | 50mA typ. For CFM models (daisy-chained CANbus): max. current internal T-junction: 2.5A |
| Operating temperature | -40 .. +80 °C |
| Storage temperature | -40 .. +85 °C |
| Measuring range | ± 30° |
| Centering function | Yes (CANout 0 = 0°), range: ±5° |
| Frequency response (-3dB) | 0 - 50 Hz, Max angle rate 500°/s |
| Accuracy (overall @20°C) | 0,07° typ. (static), 0,5° typ. (dynamic) |
| Offset error | ± 0,01° typ. (± 0,02° 2σ) after centering |
| Non linearity | Static: ± 0.06° typ., ± 0,1° 2σ, ± 0.15° max, Dynamic: ± 0,5° typ. (*) (**) |
| Sensitivity error | not applicable. Repeatability 0,05° |
| Resolution | 0,01° |
| Temperature coefficient | ± 0.003°/K typ., ± 0.005°/K (2σ) |
| Max mechanical shock | 10,000g (max 0,2ms, non-repetitive) |
| CAN interface | According to ISO 11898-1 & ISO 11898-2 (CAN 2.0 A/B), Short circuit protected |
| SAE J1939 | SAE J1939 |
| Baud rate<br>Default address<br>PGN<br>PGN cycle time<br>Priority<br>Output format<br>Internal CANbus termination | 250 kbit/s (range 250/500kbit/s)<br>80h = 128dec<br>Inclination: FF00h = 65280dec<br>100ms<br>3 (default)<br>Integer: -3000 to +3000 (X=byte 1,0; Y=byte 3,2)<br>120 Ohm on/off (default: off) |
| Boot time | < 0.5 s |
| Programming options | J1939 parameters: baud rate, device address PGN, cycle time, priority.<br>Sensor functions: internal CANbus termination |



Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000


# QG series

## QG65D-KDXYh-030H-CANJ-C(F)M-UL

J1939 output = 100*α

Clipping outside measuring range

### Transfer characteristic





### Measurement orientation

Default 0°: horizontal (label upwards), no acceleration applied. To eliminate mounting offsets the sensor can be zero-ed within ±5° tilt (by the CAN object dictionary)

Cross tilt sensitivity error:
< (0,12 * cross tilt angle)² % typ.

→ one axis <10° tilt for max. accuracy




### Connectivity (cable length ±10%)


Connection

Male only or Male & Female (internal T-junction) M12 connector (5 pins, A-coding)
( CiA303 V1.8.0 ) (Brass Nickel coated, contacts copper alloy)


A CANbus always has to be terminated properly according to customers bus topology and general CAN rules.
The sensor has an on-board internal 120 Ohm CANbus termination resistor that can be switched on by the CANopen dictionary (default: off).
Alternatively an external M12 termination resistor can be connected when using a Male & Female (internal T-junction) model.
External M12 termination resistors and T-connectors are available as accessoire, see DIS website.

Wire / pin coding

| | |
|---|---|
| Pin 1: | Shield |
| Pin 2: | Vcc |
| Pin 3: | Gnd & CAN_GND |
| Pin 4: | CAN_H |
| Pin 5: | CAN_L |




### Mechanical dimensions (indicative only)






Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

## E4ready, UL, J1939-manual, Ordering codes

Before using this device, please read this datasheet, the Manual and the Declaration of Conformity carefully (download from dis-sensors.com)

This product is E4ready and meets Automotive EMC requirements

Connect this sensor only to an approved CAN controller which must have a grounded shield. Alternativelly, connect the sensor housing to a grounded shield. All mentioned EMC standards that are met (see Declaration of Conformity) have been done with the housing connected to a grounded shield.

QG series sensors are intended to measure inclination/acceleration/tilt. Flawless function (acc. spec.) is ensured only when used within specifications. This device is not a safety component acc. to EU Machine Directive (ISO13849). For full redundancy two devices can be used. Modifications or non-approved use will result in loss of warranty and void any claims against the manufacturer.

UL & c-UL listed product (File number E312057, UL508 standards UL60947-5-2 & CSA-C22,2 No. 14)
Product Identity / Category Code Number (CCN): Industrial Control Equipment / NRKH & NRKH7
Enclosure rating: type 1, Ambient temperature: max 80 °C (see also datasheet, lowest value applies)
Electrical ratings: Intended to be used with a Class 2 power source in accordance with UL1310,
max. input Voltage 32V dc (see also datasheet, lowest value applies), max. current 200mA
Accessory Cable Assembly: Any UL-listed (CYJV/7) mating connector with mechanical locking, wire thickness of at least 30 AWG (0,05 mm²), recommended ≤23 AWG (≥0,25 mm²)

(*) Accuracy within spec : approx.. 30sec after boot-up.
(**) Dynamic accuracy figures based on Robot tests, robot performing actions representative for general mobile machine movements

Optional: for accurate mounting two factory mounted positioning pins can be mounted (Ø4mm) replacing 2x M5x25 mm.

As this device is accelerometer-based the sensor is inherent sensitive for accelerations/vibrations.
The majority of these dynamic effects will be eliminated by the on-board gyroscope.
The on-board gyroscope and Kalmann filtering are special designed to prevent the inclinometer to become significant inaccurate in dynamic situations.
Application specific testing must be carried out to check which compensation algorithm fits the application best, and whether this sensor will fulfil customers requirements.

A 1939 manual can be downloaded from the website (Type JA)

Ordering codes:
QG65D-KDXYh-030H-CANJ-CM-UL: 14007
QG65D-KDXYh-030H-CANJ-CFM-UL: 14010



Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000